

## Safety Data Sheet

### FAST SB HARDENER FOR BARRIERS

Safety Data Sheet dated: 1/30/2023 - version 1

Date of first edition: 1/30/2023



## 1. IDENTIFICATION

### Product identifier

Mixture identification:

Trade name: FAST SB HARDENER FOR BARRIERS

### Other means of identification:

Trade code: C204

### Recommended use of the chemical and restrictions on use

Recommended use: Hardener for professional/industrial use

Restrictions on use: N.A.

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: ICA North America  
169 Main Street  
West Lorne, ON  
N0L 2P0  
Canada

Responsible: regulatoryaffairs@icaspa.com

### Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire,

Exposure, or Accident Call CHEMTREC Day or Night

Within USA and Canada: 1 -800-424-9300

## 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Flammable Liquids — Category 2

Highly flammable liquid and vapour.

Eye irritation, Category 2A

Causes serious eye irritation.

Skin Sensitization, Category 1

May cause an allergic skin reaction.

Specific target organ toxicity following single exposure, Category 3

May cause drowsiness or dizziness.

### Label elements

#### Pictograms and Signal Words



Danger

### Hazard statements

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / lighting / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- 3
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- 8
- P312 Call a POISON CENTER / doctor / if you feel unwell.
- P321 Specific treatment (see safety data sheet).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.


**Dir. 2004/42/EC (VOC directive)**

This product contains max 667.52 g/l VOC.

**Hazards not otherwise classified identified during the classification process:**

None

**Additional classification information**



HMIS Health: 0 = MINIMAL  
 HMIS Flammability: 3 = Flammable liquid  
 HMIS Reactivity: 0 = MINIMAL  
 HMIS P.P.E.: Safety glasses, gloves  
 NFPA Health: 0 = MINIMAL  
 NFPA Flammability: 3 = Flammable liquid  
 NFPA Reactivity: 0 = MINIMAL  
 NFPA Special Risk: NONE

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substances**

N.A.

**Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

Qty	Name	Ident. Numb.	Classification	Registration Number
50-75 %	Ethyl acetate	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336	01-2119475103-46-XXXX
15-25 %	Toluene diisocyanate-trimethylolpropane polymer	CAS:53317-61-6 EC:500-120-8	Skin Sens. 1, H317; Eye Irrit. 2A, H319	
3-10 %	Aromatic polyisocyanate	CAS:9017-01-0	Skin Sens. 1, H317; Eye Irrit. 2A, H319	
3-10 %	N-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119485493-29-XXXX

---

## 4. FIRST AID MEASURES

### Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

### Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

Suitable extinguishing media:

### Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: N.A.
- Oxidizing properties: No

### Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus .
  - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
  - Move undamaged containers from immediate hazard area if it can be done safely.
- 

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Remove persons to safety.
- See protective measures under point 7 and 8.

### Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
  - Wash with plenty of water.
- 

## 7. HANDLING AND STORAGE

### Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Do not use on extensive surface areas in premises where there are occupants.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

- Always keep in a well ventilated place.
  - Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
-

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
 Avoid accumulating electrostatic charge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.  
 Safety electric system.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
Ethyl acetate CAS: 141-78-6	EU		C		400			
N-butyl acetate CAS: 123-86-4	MAK	UNITED ARAB EMIRATES	C	480	100	480	100	
	MAK	ALBANIA	C	480	100	960	200	

#### Predicted No Effect Concentration (PNEC) values

	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
Ethyl acetate CAS: 141-78-6	0.2 g/kg	Food chain		
	0.148 mg/kg	Soil (agricultural)		
	0.24 mg/l	Water		
	0.02 mg/l	Water		
	1.15 mg/kg	Air		
	0.115 mg/kg	Marine water sediments		
N-butyl acetate CAS: 123-86-4	650 mg/l	Microorganisms in sewage treatments		
	0.09 mg/kg	Soil (agricultural)		
	0.18 mg/l	Water		
	0.36 mg/l	WATER, INTERMITTING RELEASE		
	0.018 mg/l	Water		
	0.981 mg/kg	Air		
	0.098 mg/kg	Marine water sediments		
	35.6 mg/l	Microorganisms in sewage treatments		

#### Derived No Effect Level (DNEL) values

	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
Ethyl acetate CAS: 141-78-6	1468 mg/m3		734 mg/m3	Human Inhalation	Short Term, local effects	
	1468 mg/m3		734 mg/m3	Human Inhalation	Short Term, systemic effects	
	63 mg/kg		37 mg/kg	Human Dermal	Long Term, systemic effects	
	734 mg/m3		367 mg/m3	Human Inhalation	Long Term, local effects	
	734 mg/m3		367 mg/m3	Human Inhalation	Long Term, systemic effects	
			4.5 mg/kg	Human Oral	Long Term, systemic effects	
N-butyl acetate				Human Dermal	Short Term, local effects	

11 mg/kg	6 mg/kg	Human Dermal	Short Term, systemic effects
600 mg/m3	300 mg/m3	Human Inhalation	Short Term, local effects
600 mg/m3	300 mg/m3	Human Inhalation	Short Term, systemic effects
	2 mg/kg	Human Oral	Short Term, systemic effects
11 mg/kg	6 mg/kg	Human Dermal	Long Term, local effects
		Human Dermal	Long Term, systemic effects
300 mg/m3	35.7 mg/m3	Human Inhalation	Long Term, local effects
300 mg/m3	35.7 mg/m3	Human Inhalation	Long Term, systemic effects
	2 mg/kg	Human Oral	Long Term, systemic effects

Appropriate engineering controls: N.A.

#### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Liquid Transparent

Odour: Characteristic

Odour threshold: N.A.

pH: Not Relevant

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 80 °C (176 °F)

Flash point:  $-18^{\circ}\text{C} \leq T < 23^{\circ}\text{C}$

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 0.98 g/ml

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: No

Solid/gas flammability: data not applicable

VOC content (g/L) in the product (2010/75/UE) 667.52

VOC content % in the product (2010/75/UE) 68.11

### Other information

Substance Groups relevant properties N.A.

Miscibility: N.A.

Fat Solubility: N.A.  
Conductivity: N.A.

---

## 10. STABILITY AND REACTIVITY

### Reactivity

It may generate dangerous reactions (See subsections below)

### Chemical stability

It may generate dangerous reactions (See subsections below)

### Possibility of hazardous reactions

None.

### Conditions to avoid

Avoid accumulating electrostatic charge.

### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### Hazardous decomposition products

None.

---

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: Specific target organ toxicity following single exposure, Category 3(H336)
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

#### Toxicological information on main components of the mixture:

Ethyl acetate	a) acute toxicity	LD50 Oral Rat 4934 mg/kg
	b) skin corrosion/irritation	LD50 Skin Rabbit > 20000 mg/kg
	j) aspiration hazard	LC50 Inhalation Vapour Rat > 22.5 mg/l 6h
N-butyl acetate	a) acute toxicity	LD50 Oral Rat 10760 mg/kg
	b) skin corrosion/irritation	LD50 Skin Rabbit > 14112 mg/kg
	j) aspiration hazard	LC50 Inhalation Vapour Rat > 21.1 mg/l 4h

#### Substance(s) listed on the IARC Monographs:

None

#### Substance(s) listed as OSHA Carcinogen(s):

None

#### Substance(s) listed as NIOSH Carcinogen(s):

None

#### Substance(s) listed on the NTP report on Carcinogens:

## 12. ECOLOGICAL INFORMATION

### Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

### List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

### List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Ethyl acetate	CAS: 141-78-6 - EINECS: 205- 500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : EC50 Daphnia 165 mg/L 48h - Daphnia magna  a) Aquatic acute toxicity : LC50 Fish 230 mg/L 96h - Fish b) Aquatic chronic toxicity : NOEC Algae > 100 mg/L b) Aquatic chronic toxicity : NOEC Daphnia 2.4 mg/L - Daphnia pulex
N-butyl acetate	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : EC50 Daphnia 44 mg/L 48h  b) Aquatic chronic toxicity : IC50 Algae 397 mg/L 72h - Alga a) Aquatic acute toxicity : LC50 Fish 18 mg/L 96h - Fish

### Persistence and degradability

Component	Persistence/Degradability:	Value
Ethyl acetate	Readily biodegradable	0
Toluene diisocyanate-trimethylolpropane polymer	Non-readily biodegradable	0
N-butyl acetate	Readily biodegradable	0

### Bioaccumulative potential

Component	Value
N-butyl acetate	1.27

### Mobility in soil

N.A.

### Other adverse effects

N.A.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## 14. TRANSPORT INFORMATION

### UN number

ADR-UN number: 1866

DOT-UN Number: UN1866

IATA-Un number: 1866

IMDG-Un number: 1866

### UN proper shipping name

ADR-Shipping Name: RESIN SOLUTION, flammable (vapour pressure at 50 °C more than 110 kPa)

DOT Proper Shipping Name: Resin solution, flammable

IATA-Technical name: RESIN SOLUTION flammable

IMDG-Technical name: RESIN SOLUTION flammable

### Transport hazard class(es)

ADR-Class: 3

DOT Hazard Class: 3

IATA-Class: 3

IMDG-Class: 3

**Packing group**

ADR-Packing Group: II

ADR exempt: II

IATA-Packing group: II

IMDG-Packing group: II

**Environmental hazards**

Marine pollutant: No

Environmental Pollutant: N.A.

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

N.A.

**Special precautions**

Department of Transportation (DOT):

DOT-Special Provision(s): 149, 383, B52, IB2, T4, TP1, TP8

DOT Label(s): 3

DOT Symbol: N/A

DOT Cargo Aircraft: N/A

DOT Passenger Aircraft: N/A

DOT Bulk: N/A

DOT Non-Bulk: N/A

Road and Rail (ADR-RID):

ADR exempt: No

ADR-Label: 3

ADR - Hazard identification number: 33

ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: -

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-EMS: F-E, S-E

IMDG-MFAG: N/A

---

**15. REGULATORY INFORMATION**

**USA - Federal regulations**

**TSCA - Toxic Substances Control Act**

**TSCA inventory:**

All the components are listed on the TSCA inventory

**TSCA listed substances:**

Ethyl acetate	is listed in TSCA	Section 8b
Toluene diisocyanate-trimethylolpropane polymer	is listed in TSCA	Section 8b
Aromatic polyisocyanate	is listed in TSCA	Section 8b Section 12b
N-butyl acetate	is listed in TSCA	Section 8b



**SARA - Superfund Amendments and Reauthorization Act**

**Section 302 - Extremely Hazardous Substances:**

No substances listed

**Section 304 - Hazardous substances:**

Ethyl acetate  
N-butyl acetate

**Section 313 - Toxic chemical list:**

No substances listed

**CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**

**Substance(s) listed under CERCLA:**

Ethyl acetate	Reportable quantity:	5000	pounds
N-butyl acetate	Reportable quantity:	5000	pounds
	Reportable quantity for mixture:	8478.46	pounds

**CAA - Clean Air Act**

**CAA listed substances:**

Ethyl acetate	is listed in CAA	Section 111
N-butyl acetate	is listed in CAA	Section 111

**CWA - Clean Water Act**

**CWA listed substances:**

Ethyl acetate	is listed in CWA	Section 304
N-butyl acetate	is listed in CWA	Section 304 Section 311

**USA - State specific regulations**

**California Proposition 65**

**Substance(s) listed under California Proposition 65:**

No substances listed

**Massachusetts Right to know**

**Substance(s) listed under Massachusetts Right to know:**

Ethyl acetate  
N-butyl acetate

**Pennsylvania Right to know**

**Substance(s) listed under Pennsylvania Right to know:**

Ethyl acetate  
N-butyl acetate

**New Jersey Right to know**

**Substance(s) listed under New Jersey Right to know:**

Ethyl acetate  
N-butyl acetate

---

**16. OTHER INFORMATION**

<b>Code</b>	<b>Description</b>
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

<b>Code</b>	<b>Hazard class and hazard category</b>	<b>Description</b>
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A

A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3

Safety Data Sheet dated: 1/30/2023 - version 1

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

**Legend to abbreviations and acronyms used in the safety data sheet:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.



---

## EXPOSURE SCENARIO: ETHYL ACETATE

### Exposure scenario number: 2

Attachment to safety data sheet as per Article 31 (section 7) of (EC) 1907/2006 - REACH regulation

Identified uses of the component **Ethyl acetate**

CAS: 141-78-6 , EC: 205-500-4, INDEX: 607-022-00-5 e Nr. REACH: 01-2119475103-46-XXXX

Product for industrial or professional use in the formulation of thinners, paints, additives, hardeners and pastes for painting products.

### Data of substance

Physical state at 20°C	Liquid
Boiling point	77°C (1.013 hPa)
Vapour pressure	98 hPa (20°C)
Biodegradation	Readily biodegradable (Method BOD)

### Company data

Annual amount per site	1266901 Kg
Daily amount per site	5931.07 Kg
Yearly days of use	235 days
Duration and frequency of activity	480 min 5 days per week
Average temperature of use	20 °C
Process pressure	Ambient pressure
Local exhaust ventilation	Effectiveness: 70 %
Ventilation rate per hour	7
Wear chemically resistant gloves	Effectiveness: 80 %
Use of substance	Indoor use
Concentration of the substance in the products	Covers percentage substance in the product up to 100 % (unless stated differently).

### Environment factors

Emission or release factor in water	0%
Emission or release factor in soil	0%
Dimensions of receiving river	18.000 m3/day
Dilution factor river	10
Dilution factor coast	100

### Sewage treatment plant

Type of plant	Municipal sewage treatment plant
Flow rate of sewage treatment plant	2000 m <sup>3</sup> /day
Sludge Treatment	Disposal or recovery

### **General exposure**

Adopt good general ventilation norms, both natural by opening doors and windows, and forced ventilation using an electrically powered ventilation system.

Ensure that transfers of material are subject to restraining measures or suction ventilation.

Use suitable eye protection. In case of repeated exposure of the skin to the substance, wear protective gloves as per EN 374 norms.

## **1 - Short title of Exposure Scenario: Distribution of substance**

### **Main User Groups**

SU3: Industrial uses

SU22: Professional uses

### **Process categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4: Chemical production where opportunity for exposure arises

PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### **Environmental release categories**

ERC1: Manufacture of the substance

## **2 - Short title of Exposure Scenario : Formulation & (re)packing of substances and mixtures**

### **Main user groups**

SU3: Industrial uses

### **Sector of end-use**

SU10: Formulation

### **Process Categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4: Chemical production where opportunity for exposure arises

PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### **Environmental Release Categories**

ERC2: Formulation into mixture

### **3 - Short title of exposure scenario: Use in paints and related products**

#### **Main users groups**

SU3: Industrial uses

#### **Process Categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC4: Chemical production where opportunity for exposure arises

PROC7: Industrial spraying

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

#### **Environmental Release Categories**

ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

### **4 - Short title of exposure scenario: Use in paints and related products**

#### **Main user groups**

SU22: Professional uses

#### **Process Categories**

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

PROC19: Manual activities involving hand contact

#### **Environmental Release Categories**

ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

#### **Key**

**SU** Sector of use category

**PROC** Process Categories

**ERC** Environmental Release Categories

**Note: it is strongly advised against uses not covered in the exposure scenario**

**ICA S.p.A. - Regulatory affairs**

**Data elaboration: 19/09/2019**

**Version 1**



---

## EXPOSURE SCENARIO: N-BUTYL ACETATE

### Exposure scenario number: 1

Attachment to safety data sheet as per Article 31 (section 7) of (EC) 1907/2006 - REACH regulation

Identified uses of the component **N-butyl acetate**

CAS: 123-86-4 , EC: 204-658-1 , INDEX: 607-025-00-1 e Nr. REACH: 01-2119485493-29-XXXX

Product for industrial or professional use in the formulation of thinners, paints, additives, hardeners and pastes for painting products.

### Data of substance

Physical state at 20°C	Liquid
Boiling point	125°C a 1.013 hPa
Vapour pressure	11.6 mbar a 20°C
Biodegradation	Readily biodegradable (Method OCSE 301D)

### Company data

Annual amount per site	1762195 Kg
Daily amount per site	7498.70 Kg
Yearly days of use	235 days
Duration and frequency of activity	480 min 5 days per week
Average temperature of use	20 °C
Process pressure	Ambient pressure
Local exhaust ventilation	Effectiveness: 70 %
Ventilation rate per hour	7
Wear chemically resistant gloves	Effectiveness: 80 %
Use of substance	Indoor use
Concentration of the substance in the products	Covers percentage substance in the product up to 100 % (unless stated differently).

### Environment factors

Emission or release factor in water	0%
Emission or release factor in soil	0%
Dimensions of receiving river	18.000 m3/day
Dilution factor river	10
Dilution factor coast	100

### Sewage treatment plant

Type of plant	Municipal sewage treatment plant
Flow rate of sewage treatment plant	2000 m <sup>3</sup> /day
Sludge Treatment	Disposal or recovery

### **General exposure**

Adopt good general ventilation norms, both natural by opening doors and windows, and forced ventilation using an electrically powered ventilation system.

Ensure that transfers of material are subject to restraining measures or suction ventilation.

Use suitable eye protection. In case of repeated exposure of the skin to the substance, wear protective gloves as per EN 374 norms.

## **1 - Short title of Exposure Scenario: Distribution of substance**

### **Main User Groups**

SU3: Industrial uses

SU22: Professional uses

### **Process categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4: Chemical production where opportunity for exposure arises

PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### **Environmental release categories**

ERC1: Manufacture of the substance

## **2 - Short title of Exposure Scenario : Formulation & (re)packing of substances and mixtures**

### **Main user groups**

SU3: Industrial uses

### **Sector of end-use**

SU10: Formulation

### **Process Categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4: Chemical production where opportunity for exposure arises

PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### **Environmental Release Categories**



ERC2: Formulation into mixture

### **3 - Short title of exposure scenario: Use in paints and related products**

#### **Main users groups**

SU3: Industrial uses

#### **Process Categories**

PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC4: Chemical production where opportunity for exposure arises

PROC7: Industrial spraying

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

#### **Environmental Release Categories**

ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

### **4 - Breve titolo dello scenario d'esposizione: Utilizzo in vernici e prodotti correlati**

#### **Main user groups**

SU22: Professional uses

#### **Process Categories**

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

PROC19: Manual activities involving hand contact

#### **Environmental Release Categories**

ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

#### **Key**

**SU** Sector of use category

**PROC** Process Categories

**ERC** Environmental Release Categories

**Note: it is strongly advised against uses not covered in the exposure scenario**

**ICA S.p.A. - Regulatory affairs**

**Data elaboration: 03/09/2019**

**Version 1**

